



OXIDES & POWDERS

Morgans Grout Typical Characteristics Appearancepowder

DESCRIPTION

Morgans Grout is a regular coloured, tough, durable Portland cement grout for joints up to 6mm. When mixed with water it is easy to trowel and dries without noticeable shrinkage.

TYPICAL USES

- Natural stone
- · Concrete and cement
- Brickwork
- Plasterboard
- · Wall and flooring projects
- Internal and external applications

FEATURES

- Tough and durable
- · Easy-to-use DIY packs
- Complies with AS 2358-1990

APPLICATION

- 1. Pour **Morgans Grout** into a clean bucket containing 1 litre of water for every 5kg of powder and mix to a smooth paste. Allow the mix to slacken for 2-3 minutes, re-stir and the product is ready for use.
- 2. Working in small areas at a time, completely fill the joint with the aid of a smooth rubber squeegee. Compact the grout firmly into the joints.
- 3. When the grout has sufficiently hardened in the joints, polish the surface with a clean dry cloth.
- 4. The area is ready for traffic after 24 hours.

SAFETY

Wear suitable protective clothing, gloves and eye / face protection when using this product.

Code	Colour	Pack Size	Unit Barcode	Carton Barcode	Ctn/PIt
G0010120	White	20 x 1kg	9311052001510	19312852002681	45
G0010210	White	10 x 2kg	9318367031973	19312852002698	21



Specific Gravity...... 1.3-1.5

Toxic Hazard.....no

MSDS available

QUEENSLAND					
Tel +61 7 3308 5200					
Fax +61 7 3308 5201					