



Recochem Inc.
Your Partner in Formulating Solutions



OIL PRODUCTS

Diggers Ready To Use Timber Oil (Anti-Mould Formulation)

DESCRIPTION

Diggers Ready To Use Timber Oil is a READY-TO-USE low cost alternative to conventional decking oils - a unique product. Internal and external trials have shown this product to provide mould and mildew resistance.

TYPICAL USES

- Natural oil for decking
- Outdoor timber sealer and protector
- Decks, fences and retaining walls

FEATURES

- Mould, mildew and water resistant
- Ready to use – no mixing required
- Reduces the greying effect of timber
- Coverage: Softwoods/ Hardwoods: 6-8/8-10m² per litre (dependant on porosity and application technique)
- Will produce a warm, golden tone to pine and maple. Porous woods like walnut will darken considerably. Dense cabinet hardwoods will not absorb readily.

APPLICATION

New Timber

1. Clean surface with **Diggers Timber Cleaner**. Remove heavy deposits of wax and grease with **Diggers Wax & Grease Remover** or **Diggers Mineral Turpentine**.
2. Once dry coat with **Diggers Ready To Use Timber Oil**. Drying time is dependant on weather conditions but as a guideline allow approximately 24 hours between coats. Clean excess oil with a clean lint free cloth to avoid heavy build up and the surface drying sticky.

Previously Coated/Weathered Timber

1. Clean and remove previous coating by sanding the surface. Wash and coat as indicated above.

How does Linseed Oil work? When linseed oil is applied to a porous surface it fills the pores and as it is exposed to the air it gels to form a protective film. The film is generally impervious to water, heat, scratches and most stains.

NOTE: Timber exposed to the elements will have higher absorption rate.

NOTE: Soak rags in water as spontaneous ignition may occur on drying. Dispose of rags by controlled incineration or at an approved landfill.

SAFETY

Wear suitable protective clothing, gloves and eye/face protection when using this product.

Typical Characteristics

Appearancegolden-brown
viscous fluid

Specific Gravity..... 0.85

Flash Point.....typically 75°C

Boiling Point..... 190–250°C

Flammability Limit..... 0.6–7.0°C



SDS available



Code	Pack Size	Unit Barcode	Carton Barcode	Ctn/Plt
16411-61DIG	6 x 1 litre	9312852001885	19312852001882	112
16411-4DIG	4 x 4 litre	9312852001892	19312852001899	48

QUEENSLAND
Tel +61 7 3308 5200
Fax +61 7 3308 5201

NEW SOUTH WALES
Tel +61 2 8709 9600
Fax +61 2 9791 5066

VICTORIA
Tel +61 3 9408 4144
Fax +61 3 9408 4155

SOUTH AUSTRALIA
Tel +61 8 8222 1333
Fax +61 8 8260 7883

WESTERN AUSTRALIA
Tel +61 8 9352 3000
Fax +61 8 9352 3033

© Copyright Recochem Inc. All rights reserved. All content remains the property of Recochem Inc. All other trademarks mentioned are trademarks or registered trademarks of their respective owners. All text, images, graphics and PDF files are subject to the copyrights and intellectual property rights of Recochem Inc. Separate to the purpose of review and private use, this information cannot be used without written permission from Recochem. Information contained herein is for general information only and should not be used as an infallible to a product's specification and or performance.