SOLVENTS & THINNERS



TYPICAL CHARACTERISTICS

Appearanceclear viscous liquid

Odour.....sweet

Specific Gravity.....1.11

Boiling Point197-225°C

Flash Point......103°C

SDS available



DIGGERS Paint Stripper Domestic

DESCRIPTION

DIGGERS Paint Stripper domestic formulation is a low odour, biodegradable, methylene chloride free alternative that deeply penetrates and quickly lifts paint for easy removal.

TYPICAL USES

Suitable for domestic, industrial, automotive and marine applications Effective on oil and water based paints, acrylics, varnishes and epoxies Timber, metal and masonry surfaces Indoor/outdoor use

FEATURES

- Water wash-up
- Biodegradable
- Low odour
- Gel formula for vertical surfaces (thixotropic)
- Works in 30 minutes and stays wet for 24hrs allows you to complete a whole project in one application
- Domestic Strength removes several layers in a single application
- · Methylene chloride free contains no flammable ingredients
- 1 litre will cover 2m²

APPLICATION

Always shake/mix well before use. Apply a thick coat using a paint brush or roller. The paint stripper will begin to work after approximately 30 minutes as it penetrates into the paint and softens it. Unlike Methylene Chloride based paint strippers, DIGGERS Paint Stripper Domestic Formulation will not make the paint blister but will gently soften the paint so that it can be scraped off. The time required for full penetration of the stripper into the painted surface will depend on the quality of the paint and the number of coats to be removed.



Use a paint scraper or steel wool to remove paint before paint rehardens. If paint remains after scraping, apply a second coat. To prevent damage on delicate timbers use a non-metallic scourer to remove paint. If performing a clear finish, conduct a trial on an inconspicuous area. Do not use on plastic, rubber, linoleum or fibreglass surfaces. Do not use hot air guns or torches with paint stripper.

Wash surface with water to remove residue. Alternatively use DIGGERS Methylated Spirits if surface is affected by water or there is a danger of raising or swelling the timber. Allow surfaces to dry thoroughly before redecorating.

SAFETY

Follow safety directions on the product label. Wear suitable protective clothing, gloves and eye/face protection when using this product.

Code	Pack Size	Unit Barcode	Carton Barcode	Ctn/Plt
16883-61DIG	6 x 1 litre	9312852002790	19312852003541	96

OUEENSLAND	NEW SOUTH WALES	VICTORIA	SOUTH AUSTRALIA	WESTERN AUSTRALIA
Tel +61 7 3308 5200	Tel +61 2 8709 9600	Tel +61 3 9408 4144	Tel +61 8 8222 1333	Tel +61 8 9352 3000
Fax +61 7 3308 5201	Fax +61 2 9791 5066	Fax +61 3 9408 4155	Fax +61 8 8260 7883	Fax +61 8 9352 3033

© Copyright Recochem Inc. All rights reserved. All content remains the property of Recochem Inc. All other trademarks mentioned are trademarks or registered trademarks or their respective owners.

All text, images, graphics and PDF files are subject to the copyrights and intellectual property rights of Recochem Inc. Separate to the purpose of review and private use, this information cannot be used without written permission from Recochem. Information contained herein is for general information only and should not be used as an infallible to a product's specification and or performance.