OIL PRODUCTS





DIGGERS Timber Oil Quicker Dry Concentrate (Pale Boiled Linseed)

DESCRIPTION

DIGGERS Timber Oil Quicker Dry Concentrate is a TREATED linseed oil with ADDED DRYING AGENTS to speed up drying time.

TYPICAL USES

- Timber sealer and protector for indoor furniture and cabinets
- · Wooden tool handles and sporting equipment
- Thinner for artists' oil paints

FEATURES

- Added drying agents (dries faster than DIGGERS Timber Oil Raw Concentrate)
- Creates a finish that is generally impervious to water, heat, scratches and most stains
- · Helps aid brushing when added to oil based paints
- Dries lighter in colour than DIGGERS Timber Oil Raw Concentrate

APPLICATION

Timber Protection

- 1. Clean and dry surface. Mix DIGGERS Timber Oil Quicker Dry Concentrate 50:50 with DIGGERS Mineral Turpentine for increased timber protection.
- Apply two coats with a brush, roller or spray gun. DIGGERS Timber
 Oil Quicker Dry Concentrate should be applied in very thin coats and
 rubbed well into the wood. It is important to allow drying time between
 coats. Clean excess oil with a clean lint free cloth to avoid the surface
 drying sticky.*

How does Linseed Oil work? When linseed oil is applied to a porous surface it fills the pores and as it is exposed to the air it gels to form a protective film. The film is generally impervious to water, heat, scratches and most stains.

*NOTE: Soak rags in water as spontaneous ignition may occur on drying. Dispose of rags by controlled incineration or at an approved landfill.

SAFETY

Wear suitable protective clothing, gloves and eye/face protection when using this product.

Code	Pack Size	Unit Barcode	Carton Barcode	Ctn/Plt
16406-61DIG	6 x 1 litre	9311052002050	19312852002056	112
16406-4DIG	4 x 4 litre	9311052000209	19312852002049	48
16406-20	1 x 20 litre	9312852000161	N/A	32



QUEENSLAND	NEW SOUTH WALES	VICTORIA	SOUTH AUSTRALIA	WESTERN AUSTRALIA
Tel +61 7 3308 5200	Tel +61 2 8709 9600	Tel +61 3 9408 4144	Tel +61 8 8222 1333	Tel +61 8 9352 3000
Eav ±61 7 3308 5201	Eav ±61 2 0701 5066	Eav ±61 3 0408 4155	Eav ±61 9 9260 7993	Env ±61 8 0352 3033