SOLVENTS & THINNERS





DIGGERS Xylene

DESCRIPTION

DIGGERS Xylene is a specialty solvent for thinning and stripping sealers.

TYPICAL USES

- Thinning for solvent based acrylic (SBA) sealers
- Stripping solvent based acrylic (SBA) sealers
- Removes grease, oil and dirt

FEATURES

- High solvency power
- Mid-to-slow evaporation rate

APPLICATION

Thinning Sealers

• Always follow the manufacturer's directions when thinning sealers.

Stripping Sealers

Test a small area first before taking on the whole job. Saturate a lint free cloth and wipe the surface using a clean part of the cloth for each wipe. Do NOT use on painted surfaces or Perspex.

SAFETY

Wear suitable protective clothing, gloves and eye/face protection when using this product.

TYPICAL CHARACTERISTICS

Appearance colourless liquid		
Specific Gravity	0.87	
Flash Point	26oC	
Boiling Point	136–145oC	
Flammability Limit		
Auto Ignition Point	432–530oC	

🔰 SDS available



Code	Pack Size	Unit Barcode	Carton Barcode	Ctn/Plt
16030-61DIGN	6 x 1 litre	9311052002098	19312852002018	96
16030-4DIG	4 x 4 litre	9311052002104	19312852002025	45
16030-20	1 x 20 litre	9312852002240	N/A	32

QUEENSLAND Tel +61 7 3308 5200 Fax +61 7 3308 5201

NEW SOUTH WALES Tel +61 2 8709 9600 Fax +61 2 9791 5066

VICTORIA Tel +61 3 9408 4144 Fax +61 3 9408 4155 **SOUTH AUSTRALIA** Tel +61 8 8222 1333 Fax +61 8 8260 7883 WESTERN AUSTRALIA Tel +61 8 9352 3000 Fax +61 8 9352 3033

© Copyright Recochem Inc. All rights reserved. All content remains the property of Recochem Inc. All other trademarks mentioned are trademarks or registered trademarks of their respective owners. All text, images, graphics and PDF files are subject to the copyrights and intellectual property rights of Recochem Inc. Separate to the purpose of review and private use, this information cannot be used without written permission from Recochem. Information contained herein is for general information only and should not be used as an infallible to a product's specification and or performance.