

## DIGGERS™ Paint Stripper Domestic

### DESCRIPTION

DIGGERS™ Paint Stripper domestic formulation is a low odour, biodegradable, methylene chloride free alternative that deeply penetrates and quickly lifts paint for easy removal.

### TYPICAL USES

- Suitable for domestic, industrial, automotive and marine applications
- Effective on oil and water based paints, acrylics, varnishes and epoxies
- Timber, metal and masonry surfaces
- Indoor/outdoor use

### FEATURES

- Water wash-up
- Biodegradable
- Low odour
- Gel formula for vertical surfaces (thixotropic)
- Works in 30 minutes and stays wet for 24hrs – allows you to complete a whole project in one application
- Domestic Strength – removes several layers in a single application
- Methylene chloride free - contains no flammable ingredients
- 1 litre will cover 2m<sup>2</sup>

### APPLICATION

Always shake/mix well before use. Apply a thick coat using a paint brush or roller. The paint stripper will begin to work after approximately 30 minutes as it penetrates into the paint and softens it. Unlike Methylene Chloride based paint strippers, DIGGERS™ Paint Stripper Domestic Formulation will not make the paint blister but will gently soften the paint so that it can be scraped off. The time required for full penetration of the stripper into the painted surface will depend on the quality of the paint and the number of coats to be removed.

Use a paint scraper or steel wool to remove paint before paint rehardens. If paint remains after scraping, apply a second coat. To prevent damage on delicate timbers use a non-metallic scourer to remove paint. If performing a clear finish, conduct a trial on an inconspicuous area. Do not use on plastic, rubber, linoleum or fibreglass surfaces. Do not use hot air guns or torches with paint stripper.

Wash surface with water to remove residue. Alternatively use DIGGERS™ Methylated Spirits if surface is affected by water or there is a danger of raising or swelling the timber. Allow surfaces to dry thoroughly before redecorating.

### SAFETY

Follow safety directions on the product label. Wear suitable protective clothing, gloves and eye/face protection when using this product.

### TYPICAL CHARACTERISTICS

Appearance .....clear viscous liquid  
Odour .....sweet  
Specific Gravity.....1.11  
Boiling Point ..... 197-225°C  
Flash Point. ....103°C



SDS available

Code	Pack Size	Unit Barcode	Carton Barcode	Ctn/Plt
16883-61DIG	6 x 1 litre	9312852002790	19312852003541	96

